



Reference No. SE-S-2300498R1

## DCL Outlet and DCL Plug

**Type designation:** DCL plug BBV58748

Certificate holder: Elko AS

Sandstuveien 68 0680 Oslo, Norway

The product complies with

the standard(s):

EN 61995-1:2008+A1+A11 EN 61995-2:2009+A1

**Date of expiry:** 04 May, 2028

**EU Directive information:** According to the principle of presumption of conformity, this certificate

constitutes support for an EC Declaration of Conformity and CE marking

according to the Low Voltage Directive 2014/35/EU.

Additional information in Appendix

Certification Body: Intertek Semko AB, Product Certification Place: Kista - Stockholm

Signed: Date: 27 November, 2023

Anneli Averland Johansson

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB Page 1 of 3



## **APPENDIX:**

Reference No. SE-S-2300498R1

**Technical Data:** 

Type designation DCL plug BBV58748

Rating 6A 250V AC Trademark ELKO

*Test Report* REP008092 - PRJ0024961

*Product information* Rewirable for flexible cable 3G0.5-1.0mm<sup>2</sup>. Screw terminals.

Standard sheet 1-2

Additional models

Product DCL Outlet and DCL Plug

Pos. No.

Model / Type Ref. DCL Wall; Couplers: 15003 (Screw terminals) QGH60134 and QGH60136

(Screwless terminals); Covers: RS and Plus design: S1A11148 (inner center cover), BBV58759 (outer center cover) One design: PKR2809002 (inner

center cover), PKR1053602 (outer center cover)

Rating 6A 250V AC

*Principal characteristics* Flush type, rewirable, for rigid (stranded) conductors 1.0-2.5mm<sup>2</sup>. Mounting

in wall boxes with 60mm fixing distance. Standard sheet 1-1 and 1-2. IP 20 or IP21 when mounted in declared surface box: 1-gang surface box Plus. 1-gang

surface box RS. 1-gang surface box One.

Additional information:

IP21 for the DCL Wall when installed in declared surface box:

1-gang surface box Plus, 1-gang surface box RS, 1-gang surface box One

Product DCL Outlet and DCL Plug

Pos. No. 2

Model / Type Ref. DCL Ceiling; Couplers: 15003 (Screw terminals) QGH60134 and QGH60136

(Screwless terminals); Covers: BBV58744 (inner center cover) BBV58743

(outer center cover)

Rating 6A 250V AC

Principal characteristics DCL outlet and DCL plug. Flush type, rewirable, for rigid (stranded)

conductors 1.0-2.5mm<sup>2</sup>. Mounting in ceiling boxes with 70mm fixing distance, a 10mm spacer can be fitted, equipped with device (hook) for

hanging up to 15kg. Standard sheet 1-1 and 1-2.

Product DCL Outlet and DCL Plug

Pos. No.

Model / Type Ref. DCL spacer: L3636

Rating

Principal characteristics Frame for making additional space for DCL ceiling.

Intertek Semko AB Page 2 of 3

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



## **APPENDIX:**

Reference No. SE-S-2300498R1

Product DCL Outlet and DCL Plug

Pos. No. 4

Model / Type Ref. DCL Ceiling Outlet: Coupler: 15003 (Screw terminal), Covers: BBV59755

(inner center cover), GDE5636102 (outer center cover)

Rating 6A 250V AC

Principal characteristics DCL Ceiling outlet flush type, rewirable, for rigid (stranded) conductors

1.0-2.5mm<sup>2</sup>. For mounting in existing ceiling boxes with centred screw tower

for hook, a 10mm spacer can be fitted; standard sheet 1-1

Manufacturing Sites: Schneider Electric Elda S.A.

ul. Bugno 1

78-400 Szczecinek Poland

AS M ja P Nurst Ümarmäe 3 Kärdla Hiiumaa 92414, Estonia

According to the principle of presumption of conformity, this certificate, which includes production control, constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

This presumption can expire before end of validity of this certificate due to new issued Standard or Amendment and changes within the EU legislation.

The certificate applies for countries that have sanctioned the use of plugs/outlets according to subject standard sheet and component standard.

This certificate is based on a certificate with ref. No. No. P23227025/A2 dated 16 November 2023 issued by Nemko Group AS according to the Nordic Certification Service agreement.

This certificate replaces the S certificate SE-S-2300498 dated 04 May 2023 due to corrected specifications and information for Position No. 1 and No. 3.

Certification Body: Intertek Semko AB, Product Certification Place: Kista - Stockholm

Signed: Date: 27 November, 2023

Anneli Averland Johansson

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB Page 3 of 3