



gorenje

INFORMATIONSBLAG

MODELL	DK63CLI
Annual Energy Consumption - AEC_{hood}	119,5 kWh/a
ENERGIKLASS	D
Fluid Dynamic Efficiency - FDE	13,9 %
Fluid Dynamic Efficiency class	D
Light Efficiency - LE_{hood}	8,6 lux/W
Lighting Efficiency Class	E
Grease Filtering Efficiency - GFE_{hood}	57,0 %
Grease Filtering Efficiency class	E
A-weighted Sound Power Emission at minimum speed	355 m ³ /h
Maximum Air Flow in normal use	545 m ³ /h
Air Flow at intensive/boost setting	-
A-weighted Sound Power Emission at minimum speed	54 dB(A) re 1pW
A-weighted Sound Power Emission at maximum speed	64 dB(A) re 1pW
A-weighted Sound Power Emission at intensive or boost speed	-
Power consumption in on mode - P_o	-
Power consumption in standby mode - P_s	-
Time increase factor	1,5
Energy Efficiency Index - EEI	93,3
Measured air flow rate at best efficiency point - Q_{bep}	290,0 m ³ /h
Measured air pressure at best efficiency point - P_{bep}	285,0 Pa
Maximum air flow - Q_{max}	545 m ³ /h
Measured electric power input at best efficiency point - W_{bep}	165,0 W
Nominal power of the lighting system - W_L	40,0 W
Average illumination of the lighting system on the cooking surface - $E_{average}$	342,0 lux