

KCV9NE2

linea Aesthetic

EAN13: 8017709257194

Subfamily: Decorative wall hood

Aesthetics: Linea

Color: Steel / Black Glass

Hood width: 90 cm

Energy efficiency class (EEC): B



TYPE



- Hood width: 90 cm
- Electronic control: Yes

- Product family: Hood
- Subfamily: Decorative wall hood
- Extraction: Expulsion
- Perimeter extraction: Yes

AESTHETICS

- Aesthetics: Linea
- Design: Angled
- Material: Glass
- Glass Type: Black

- Serie: New
- Color: Steel / Black Glass
- Type of steel: Brushed

CONTROLS



- Display: Yes

- Control setting: Touch control
- Led color: Ice

PROGRAMS / FUNCTIONS



- No. of speeds: 3

TECHNICAL FEATURES



- Light Power: 1 W
- Free outlet maximum capacity: 815 m³/h
- No. of filters: 1
- Filter replacement indicator: Yes
- Minimum distance from GAS hob: 467 mm
- Non return valve: Yes

- No. of lights: 2
- Light type: LED
- Dimmer mode: Yes
- Motor power: 275 W
- Anti-grease filters: Stainless steel
- Minimum distance from ELECTRIC hob: 467 mm
- Vent outlet: 150 mm

SPEED 1

- Extraction rate IEC 61591: 218 m³/h
- Power: 82 W

- Noise level IEC 60704-2-13: 42 dB(A)

SPEED 2

- Extraction rate IEC 61591: 322 m³/h
- Power: 142 W

- Noise level IEC 60704-2-13: 63 dB(A)

SPEED 3

- Extraction rate IEC 61591: 600 m³/h
- Power: 268 W

- Noise level IEC 60704-2-13: 65 dB(A)

INTENSIVE SPEED

- Extraction rate (IEC 61591): 734 m³/h
- Power: 268 W

- Noise level IEC 60704-2-13: 70 dB(A)

PERFORMANCE / ENERGY LABEL

B

- Grease Filtering Efficiency Class (GFEC): G
- Annual Efficiency Consumption (AEChood): 59.9 KWh/year
- Grease Filtering Efficiency (GFE): 42.2 %
- Air flow at maximum speed (Qmax): 600 m³/h
- Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 42 dB(A)
- Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A)
- Measured air flow rate at best efficiency point (Qbep): 384 m³/h
- Measured electric power input at best efficiency point (Wbep): 160 W

- Sound power level at highest setting (Lwa): 65 dB(A)

- Energy efficiency class (EEC): B
- Fluid Dynamic Efficiency class (FDEC): A
- Lighting Efficiency Class (LEC): A
- Fluid Dynamic Efficiency (FDE): 28.6
- Lighting Efficiency (LE): 99.1 lux/W
- Air flow at minimum speed (Qmin): 218 m³/h
- Air flow at boost speed (Qboost): 734 m³/h
- Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 65 dB(A)
- Power Consumption in Off mode (Po): 0.49 W
- Energy Efficiency Index (EEI): 57
- Measured air pressure at best efficiency point (Qbep): 428 Pa
- Normal Power of the light system (WI): 2 W
- Average illumination of the light on the cooking surface (Emiddle): 218 lux

ELECTRICAL CONNECTION

- Electrical connection rating: 278 W
- Frequency (Hz): 50-60 Hz

- Voltage: 220-240 V

OPTIONAL

- Charcoal filter: KITFC906

VERSIONS

- KCV9BE2: Steel / White Glass

- KCV9SE2: Steel / Glass

For availability in specific countries please contact your [local agent](#) .

