



Allmän information

Typ armatur	Väggarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Typ ljuskälla	LED modul + driver
Netto / Bruttovikt armatur	1,64kg / 1,94kg
Förpackning mått [cm]	31x16x15,5
LED	Philips LED SLM C 840 1203 L09 1619 G7
Drivdon	Osram OTi DALI 15/220 240/1A0 LT2 4052899324879
Led modul effekt	6,7W
Armatur effekt	8,8W
Lumen modul	1121lm
Lumen ut	696lm
Led modul effekt	167,3lm/W
Armaturens effekt	79,1lm/W
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
Energieffektivitetsindex (EEI)	A++
Effektfaktor	PF 0,85
Ta nominel:	+25°C
Inrush current	5A / 45µs
Antal armaturer på automatsäkring	B 10A: 80, B 16A: 130, C 10A: 134, C 16A: 220

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

