


Art	E-nr	Färg	RAL
5180AL	7749530	ALUMINIUM	9006
5180GR	7749531	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Glas - PMMA, frostat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	5,81kg / 6,81kg
Förpackning mått [cm]	93x16x16
3xLED moduler	Philips Strip OC 0.5ft 550lm 8xx FC LV5 3K (☞ Produktblad)
Drivdon	Philips Xitanium 8W 0,2A 40V TE SC 230V (☞ Produktblad)
Külső ellenőrzés	Philips Xitanium TE (Användarhandbok)
Led modul effekt	6,5W
Armatur effekt	8,8W
Lumen modul	1175lm
Lumen ut	706lm
Led modul effekt	180,8lm/W
Armaturens effekt	80,2lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>70 000h
Energieffektivitetsindex (EEI)	 / ☞ EPREL
Effektfaktor	PF 0,90
THD-faktor	20%
Ta nominel:	25°C
Inrush current	1,65A / 16,5µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

