


Art	E-nr	Färg	RAL
2400AL	7749599	ALUMINIUM	9006
2400GR	7749600	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	7,94kg / 8,66kg
Förpackning mått [cm]	57x44,5x13,5
LED	Cree DK200305 V3 JB2835 3V 3K (☞ Produktblad)
Led modul effekt	5,2W
Armatur effekt	6,9W
Lumen modul	978lm
Lumen ut	531lm
Led modul effekt	188,1lm/W
Armaturens effekt	77lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>72 000h
Energieffektivitetsindex (EEI)	 / ☞ EPREL
Effektfaktor	PF 0,8
THD-faktor	10%
Ta nominal:	+25°C
Inrush current	2A / 50µsec

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer