

Document of Performance According to Regulation (EU) 305/2011

Aduro 14

Roomheater burning solid fuel <u>without</u> hot water supply.

EN 13240:2001/A2:2004/AC:2007

DoP No: 14 0014

Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk, info@aduro.dk, <a href="mailto:Tel:" Tel:" Tel

System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.

Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.

performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report:</u>
RRF- 40 13 3337
300-ELAB-1981-NS

Declared performance

Geolated performance	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance marked with * is for installation with isolated pipe	rear = 150/*70
*	sides = 250
	front = 1000
	corner mounting = 80
Risk of burning fuel falling out	Pass
Emission of combustion products	CO[0.06 %]
Surface temperature	Pass
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output	T [270 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	6,5kW
Room heating output	6,5 kW
Water heating output	"" kW
Energy efficiency	η [80,4 %]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS Hasselager, 25-10-2013