

PRODUCT INFORMATION



TFM 860

Item number: 513.35.1061.2

ANUAL ENERGY CONSUMPTION (AEC_{hood})	89,5 kWh/a
ENERGY EFFICIENCY CLASS (EEI_{class})	C
FLUID DYNAMIC EFFICIENCY (FDE_{hood})	16,3 %
FLUID DYNAMIC EFFICIENCY CLASS (FDE_{class})	D
LIGHTNING EFFICIENCY (LE_{hood})	18,8 lux/W
LIGHTNING EFFICIENCY CLASS (LE_{class})	C
GREASE FILTERING EFFICIENCY (GFE_{hood})	91,2 %
GREASE FILTERING EFFICIENCY CLASS (GFE_{class})	B
MINIMUM AIRFLOW (Q_{min})	300 m ³ /h
MAXIMUM AIRFLOW (Q_{max})	600 m ³ /h
AIRFLOW – BOOST (Q_{boost})	700 m ³ /h
MINIMUM SOUND POWER LEVEL ($L_{WA min}$)	50 dBA
MAXIMUM SOUND POWER LEVEL ($L_{WA max}$)	65 dBA
SOUND POWER LEVEL – BOOST ($L_{WA boost}$)	67 dBA
POWER CONSUMPTION OFF-MODE (P_0)	0,29 W
STANDBY POWER (P_s)	0,29 W
HEIGHT	300 mm*
DEPTH	277 mm*
WIDTH	495 mm*

*All measures are with a tolerance on +/- 0.5 mm

Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014"

PRODUCT INFORMATION



TFM 880

Item number: 513.35.1081.2

ANUAL ENERGY CONSUMPTION (AEC_{hood})	89,5 kWh/a
ENERGY EFFICIENCY CLASS (EEI_{class})	C
FLUID DYNAMIC EFFICIENCY (FDE_{hood})	16,3 %
FLUID DYNAMIC EFFICIENCY CLASS (FDE_{class})	D
LIGHTNING EFFICIENCY (LE_{hood})	18,8 lux/W
LIGHTNING EFFICIENCY CLASS (LE_{class})	C
GREASE FILTERING EFFICIENCY (GFE_{hood})	91,2 %
GREASE FILTERING EFFICIENCY CLASS (GFE_{class})	B
MINIMUM AIRFLOW (Q_{min})	300 m ³ /h
MAXIMUM AIRFLOW (Q_{max})	600 m ³ /h
AIRFLOW – BOOST (Q_{boost})	700 m ³ /h
MINIMUM SOUND POWER LEVEL ($L_{WA min}$)	50 dBA
MAXIMUM SOUND POWER LEVEL ($L_{WA max}$)	65 dBA
SOUND POWER LEVEL – BOOST ($L_{WA boost}$)	67 dBA
POWER CONSUMPTION OFF-MODE (P_0)	0,29 W
STANDBY POWER (P_s)	0,29 W
HEIGHT	300 mm*
DEPTH	277 mm*
WIDTH	792 mm*

*All measures are with a tolerance on +/- 0.5 mm

Product fiche according to “COMMISSION DELEGATED REGULATION (EU) No 65/2014”